

C.S. # 458

Hardcopy 14-4 # 1

F.B. 16-68



68 already Reest.

#450 In Sec 30, T. 143, R. 4W

FB# 16

Cont. of C.S. # 18 For Theo.

25/30 Maple 30' N. 19° E. 54 chs.
 36/31 " 24" S. 4° 30' E. 100 "
 Stone " 34" S. 26° W. 1137 "
 " 18" S. 74° 10' W. 170 "

1 Offset North 380

1 N. 89° 59' E. 5691

2 correction S. 31' 8.773

(S. 89° 30' E. 41.17) +.133

Striking N. of cor. 472 should be 3.5-11

3 25.550

+1.165 = 41.169

Reest

Striking N. of cor. 750

M.C. 431ks. bolt

30/31 Back to sec. cor. 25/30

North 40.196

4 1/4 cor. 25/30 set 1 1/4" galv pipe 120' E. to stone

Set 1/4" pipe S. 47° E. .065 cor. Maple STUMP

5 North 6944

6 Set 1" bolt 13.056

Reset 1/2" shaft 7' in length

6 7.787

7 6.594

775 fence. 07 s.

Nail in 8' 1/2" stump

Jan. 18, 1915.

Miller July 27 1914.

Step G.H. Bath - Chapman

offsets 413
750 S.
380 N.
3745.

008.96 = 31
3700
3304
3960
3717
2430

15° 44' 32° 32'

.490 .490
61172 35269
980 4410
343 294
4 9
1327 2

1387
97735
6935
414 1387
136 80378
13 11096
1 554
1 41.302

750 1.165 41.169

40.196

6944

10600
6944 1944
3056 7787
4731 14.731
7.787

6944 5
7.787 2
6.594 6
21.325 4

32° 52' 9730613 9925866
1387 0142076 0142076
7459 9872689 10067944 1169

5.44 to fence

69

8

-2° 30' 3451

9

4.876

on island

10

+1° 35' 5.917

Over River

11

+1° 20' 4.043

Back to Δ 5 + 3056

fence E. 17'

12

S. 89° 26' E.

9.048

3.30 to
fence

Back to Δ or 1/4 cor. 25' 30

10.14 to
Fence

13

S. 89° 26' E.

12.025

+3.16

14

7.975

set 3/4" pin

15

8.509

at S. fence to E. fence

16

3° 30' 2.837

17

Left 43'

2.534

offset

.032

PUMP

handle

Balm 2 2" N. 89° 26' W. 1.20 S. 0.32

Back to Δ 14

North

10,000

13 S. fence

set 1/4" steel shaft.

N. 89° 26' W.

at slough
085 NT
fence07 N.
at slough

07 W.

8,500

19,900

1,130

12,025

.315

12,340

2,083

9,048

952

21,325

5,917

952

180

3,778

4.876

4,876

+1° 35' 5.917

12,340

29,649

11

+1° 20' 4.043

12,025

5,915

Back to Δ 5 + 3056

fence E. 17'

.315

4,042

12

S. 89° 26' E.

9.048

3.30 to
fence

21.52

12.34

39,606

2,534

33,910

1,521

31,373

2,534

2,567

506

126

2

Back to Δ or 1/4 cor. 25' 30

10.14 to
Fence

13

S. 89° 26' E.

12.025

+3.16

.03168

33,910

12,025

7,975

14

7.975

set 3/4" pin

33,877

20,000

15

8.509

at S. fence to E. fence

.033

8,509

16

3° 30' 2.837

2,837

17

Left 43'

2.534

offset

.032

PUMP

handle

31,373

Balm 2 2" N. 89° 26' W. 1.20 S. 0.32

Back to Δ 14

North

10,000

13 S. fence

set 1/4" steel shaft.

2,136

2,534

33,877

,033

33,910

N. 89° 26' W.

at slough
085 NT
fence07 N.
at slough

07 W.