

State Highway 34

PK Nail in \odot State Highway 34 [S 89° 43' E] 1102.1—Record Distance from CS 05899 NE Cor. Thomas Hayden DLC 38
1" Iron Rod
New BT: 10" Maple N11W 40.1 mkd. BT & W.I.I. Y. Tag

Gay P. Johnston

6837
2-9-79
18"

SURVEY
IN
T13S, R7W, Secs. 29 & 32 WM.
Benton County, Ore.
FOR
Willamette Ind. Inc.

Corners Found \bullet July 1978
Corners Set \circ Scale 1" = 400'
() Denotes Bearings & Distances From CS 108
[] Denotes Base Bearing
Bearings True From CS 05899

NOTE: This Survey is in the North half of Sec. 32 and the South half of Sec. 29



ALSEA RIVER

(N 20° 00' E) 163.0
N 10° 00' E 176.50

Set: 5/8" X 30" I.R. WEST 1043.45 968.45
75.0 Witness Corner
20" Alder N58W 3.5 mkd. BT & W.I.I. Y. Tag
24" Alder S55E 17.0 mkd. BT & W.I.I. Y. Tag (BT'S Bark Scribed)

New BT'S
3/4" Iron Bar
6" Alder N82E 8.0 mkd. BT & W.I.I. Y. Tag
5" Dogwood S63E 3.0 mkd. BT & W.I.I. Y. Tag

3/4" Iron Rod & Stone
29
1/4
32
FD. BT: 20" DF N36W 44.9 mkd 1/4 S32 BT & W.I.I. Y. Tag

36.61 acres MOL

973.38
368.95

(EAST 297.26)
500° 12' 38" E
604.43

1320.22

500° 13' 11" E

Set: RR Spike
S 23° 23' 50" E 124.63

18" DF S 57W 16.2 mkd. BT & W.I.I. Y. Tag
10" Alder S46E 22.8 mkd. BT & W.I.I. Y. Tag
Corner falls in \odot of rock road

S 00° 00' 39" E 209.38

S 16° 25' 28" E 47.96

S 32° 51' 02" E 297.81

S 53° 12' 29" E 42.59

S 63° 01' 38" E 109.40

S 40° 27' 56" E 105.90

S 12° 53' 54" E 131.66

S 27° 29' 11" E 97.21

S 47° 38' 30" E 63.82

Set: RR Spike in \odot of road
14" Alder S23E 18.0 mkd. BT & W.I.I. Y. Tag
12" Alder N07E 15.4 mkd. BT & W.I.I. Y. Tag (BT'S Bark Scribed)

SOUTH 718.73

Set: 5/8" X 30" I.R.
26" DF N70E 35.8 mkd. BT & W.I.I. Y. Tag
20" Alder S45E 5.8 mkd. BT & W.I.I. Y. Tag (Bark Scribed)