

C.S. # 794

Hardcopy 10-5 # 5

also see notes in file

F. B. 28-56

	N. 5° 47' W. correction E. 5 1/2"	7.990	
10		6.580	
		.690	
	Striking E. of corner	.018	Stone the
	N.E. corner of Francis Whitsman Cl.		
	Mark to Δ 9		
	S. 5° 47' E. correction W. 5 1/2"		
11		7.995	
12		8.017	
13		6.697	
14		7.994	
		.987	
	Striking E. of cor.	.024	092 W.
15		7.938	
16		8.001	
		7.983	
17		1.104	
		-.006	
	Striking E. of Pipe	.134	.130
		7.988	
18		1.414	
		+.005	
	S.E. of Whitsman Cl. Striking E. of cor.	.144	

			7.990
			6.580
			.690
			15.260
			7.995
			8.017
			6.697
			22.709
			7.994
			30.703
			.987
			31.690
			30.703
			7.938
			8.001
			7.983
			1.104
			7.988
			1.414
			1.414
			.005
			.006
			7.988
			1.414
			.005
			9.413
			1.098
			7.983
			8.001
			7.938
			34.433
			.987
			33.446
			9.413
			24.033
			.007
			24.040

15.260
 7.990
 15.260
 7.990
 15.260
 7.990
 15.260
 7.990
 15.260
 7.990

13.310
 15.260
 27.570
 .002988

0.24
 .018
 .0018
 46.91
 .00600
 .169
 \$380

offsets
 .144
 .018
 .00157 = 5 1/2"
 50.40
 1.260
 8.04
 4.560
 40.20
 54.00

.098
 .024
 .069
 .016
 .018
 .034

55

35