

C.S. # 1493

Hardcopy 11-5 # 9

also see notes in file

F. B. 53-77

FB#53

77 1493

C.S. 260 Continued

Came to  $\frac{1}{4}$  sec. cor.  $\frac{21}{28}$  T11-5

Found oak stump 3' high, found  $\frac{3}{4}$ " pipe and placed a 100# stone on N. side, Anchor rod con. at connection at ground

N.  $79^{\circ}02'E$ . 28.75,

1.24 found  $\frac{3}{4}$ " pipe, B.S. 105  $\frac{11}{12}$  measurement N. 4.35 and found  $\frac{3}{4}$ " pipe in cr. bed 10" under surface

Oak  $6^{\circ}S. 20^{\circ}E$ . 1.75 std. at E. end  
" 17" N. E. .69 not used,  $\frac{1}{2}$  cul.

Back to  $\frac{3}{4}$ " pipe B.S. on C.I. cor.

$\angle R. 4^{\circ}52\frac{1}{2}' = S. 5^{\circ}46\frac{1}{2}' W. 1.247$  to  $\frac{1}{4}$  sec. cor.

$\angle$  bet.  $\frac{3}{4}$ " pipe & Anchor rod  $75^{\circ}15\frac{1}{2}'$

From  $\frac{3}{4}$ " pipe S.  $1^{\circ}07'$  = C.S. 270  
" " " " E.  $6^{\circ}20'$  6.194  
" " " " " " 1.599  
" " " " " "  $-7^{\circ}20'$  6.367  
" " " " " " +.006

Striking W. of loop pin. 0015

Near cor. of post S.  $35^{\circ}47'E$ . 38.0 feet

Con. anchor rod at ground S.  $27^{\circ}09'W$ . 27.38'

" " " near " S.  $55^{\circ}34'W$ . 15.22

Power pole S.  $39\frac{1}{2}'W$ . 20.32'

(Near corner) Lowest staple Anchor Post S.  $71^{\circ}55'W$ . 17.44

$\frac{1}{4}$  Yew gate post N.  $66\frac{1}{2}'W$ . 17.94

Nail, bottom wire, 16' gate post N.  $5^{\circ}18'W$ . 22.65'  
+ Stone = 16'  $\frac{1}{2}$   $\frac{1}{2}$   $\frac{1}{2}$  S.  $64^{\circ}17'W$ . 9.18'

Recorded

99182	2	9939
6367	7	6194
694274		39756
595092		89451
297546		9939
595092		59634
631491794		61562166

18420015

6327  
508  
1247

78

Correct all bearings on this page 29'

Make Mill Pass

4.350	
6.156	
1.599	
<u>12.105</u>	
6.315	
.006	
<u>18.426</u>	

36°16'	
29	
<u>35°47'</u>	
26°40'	
29	
<u>27°09'</u>	
55°05'	
29	
<u>55°34'</u>	
71°26'	
29	
<u>71°55'</u>	
5°47'	
29	
<u>5°18'</u>	
63°48'	
29	
<u>64°17'</u>	

20' = C.S. 270  
S. 0° 19' E.

10.100

Found 3/4 pipe 2' E of W. road ditch  
1' S. of wire on fence W.

Cor. of Corner post N 86° W. .316

Low vert. wire on 18' post N. 24° 37' W. .718

Anchor rod near ground S. 88° 45' W. .544

Cor. of Power pole N. 81° 46' W. .336

Set a 3/4 galv. pipe S. 89° 20' W. 20' & 1907

S. 36° 13 3/4 E.

correction W. 52'

(S. 35° 21' E. 10.262) + 3° 18' 1.665

10.269 + 3° 34' 8.000

To A 16 .726

S. 36° 19' E. for other line

(S. 35° 50' E.)

17 From 3/4 pipe & road .1907 E. of Yates S.E. cor

B.S. at N.W. cor. of Elvin Witham place

S. 89° 22' W.

Correction N. 02 1/2'

(S. 89° 24 1/2' W. 43.815)

23 1/2 E C.S. 270

18 L.L. 1° 18 1/2' + 6° 7.234

19 L.R. 1° 47' - 4° 20' 5.702

20 - 4° 10' 2.922

21 - 4° 15' 5.756

22 0° 4.291

23 + 2° 35' 4.086

offset  
1.645.  
offset  
.177 N.  
offset  
.097 N.

S. 89° 24' W.

N. 25° 06' W.

29  
24° 37'

S. 88° 16' W.

29  
88° 43'

N. 82° 15' W.

29  
81° 46'

S. 88° 51' W.

29  
S. 89° 20' W.

N. 88° 51' E. set a spike for &

36° 19'

35° 48'

31'

36° 43'

36° 12'

31'

36° 43'

36° 12'

35° 21 1/2'

50'

1026 1015 1/2 = 52'

155

1026

5240

5930

1100

1026

740

as. S. 35° 21 1/2' E.

89° 22'

S. 88° 03 1/2' W.

1° 18 1/2'

offsets  
.1645.  
.177 N.  
.013 N.  
.097 N.  
.110 N.  
.078 S.  
.032 N.

.00073 = 26'

43.816 10320000

306712

132880

+ 107 creek

88051  
31  
89° 22'

.53 to N. fence  
.404 to S fence

1.662  
- .109 = 1.088

1.553  
7.984  
7.26 E

10.263 E  
- .001  
10.262

7.192

5.693

2.973

5.740 - 030

4.291 7

25.819 8  
4.082  
29.901

Yates Road

24		+8°02'	5.337
25		+4°17'	6.423
26	L.L. 2°01'	-1°	2.226 offset .078 S.

C. S. #270 remeasured

Back to (bottle) corner S. of 100 F. Ceme.

B.S. N. 88°40½' W.

Thence N. 0°17½' W.

1494

+4°25' 6.216 To ¾" pipe

Thence N. 35°20½' W.

+3°08' 8.000

0° 1.129 ½" pipe

-2°20' 4.780

-2°30' 6.823

-0.06

Changed ¾" pipe and + on Stone S. 7654 (50.52')

5.762

8.1775 -395°

-1°25' 4.5835 To stone

From N.W. cor. of Fredley Cl.

B.S. S. 85°40½' E. Thence N. 1°00½' W.

N. 0°51' E.

S. 35°21½' E.

99019	99721	03519	29.901
5.337	6.423	2.226	5.285
693.137	299163	21114	6.405
297057	199442	7038	2.224
297057	398884	7038	43.815
495095	598326	7038	43.781
528464403	6.40507983	07833294°	.034

1500	404.003000	7
25455	28.28	
8.0025		
12048		

N. 0°20' W. to N. of Stump

99854	99917	99905	99673
798832	478	6823	2549
	99936	299715	897057
	699119	199870	398692
	399268	199840	998365
	4.7760326	799240	199346
-4°38'	99979	599430	254066
25493	4.273	6.81451815	7.2721
-1°10'	299937		6.8128
4.273	699853		
199958			
399916			
4.27210247	1852.005000		
4.58357	3707		
9992	5		
320845	17		
412515	33		
412515	24		
458212495	1009		

(60.72)

7.988
1.129
9.117
4.776
6.813
20.708

5.762
8.177
4.582
18.521

(From cl. cor. and S. 29°05' E.)  
 makes S. 85°39½' E. cl. line  
 N. 1° W. 10.395 N. and 0.006 W. of line  
 N. 50' E.