

C.S. # 2064

Hardcopy 14-5 # 6

also see notes in file

F.B. 88-67

FIB 88, PG 67

C.S. 334
Bellfountain Cemetery
2064 T-14-5

Beginning at 5/8" I. rod, Replaced with 1/2" galv. pipe,
N.W. cor. of Cemetery
(Replaced 3/4" I. rod at N.E. cor. with 1/2" pipe.)

Checked measure to be 231.77' + 23
B.S. at N.E. cor.
Thenge N. 89° 08' W. 350.00' from N.W. cor.

Set a car axle
22.64' 42'
S. 26° 10 1/4' W. -6° = 315.4 = 313.67 = 312.3
-12° 17' from property line S. 0° 05' W. = 34 bolt
+ 7° 40' - 33.07 = 591.8 x 1/4 = N. 22° 10' E.

We set 1.50' E. of S.E. cor. of Cem.
E. side of cemetery
N. 0° 27' E. + 3° 57' 343.89 = 343.07

S. 0° 27' W. - 7° 14' 381.98 = 378.94
Int. < N.W. 79° 36' (Set 5/8" I. rod to N.W. cor.)
N. 79° 09' W. - 30.5

(Not in total)
N. 66° 28 1/2' W. 133.15' 3/4" pipe
Int. < 66° 33 1/2' S.E. 395.28 = 53 = 131.62

to 1/2" pipe
to 3/4" pipe
460.18

P.I. bolt to Oak 28" N. 20° E 693

238.74
1.50
237.24
Slope 1.20
237.08 E. 1'
237.14

(Set pipe E. 23')

N. 26° 10' E.
64.42
N. 90° 22' E.
5.8907 E.

2152° 10 1/2'
22° 05 1/4'

Deck (set N. 13)
342.83

21159° 12 1/2'
790.364

N. 0° 05' E.
66.331
N. 66° 28 1/2' W.
120.40
N. 79° 09' W.
150.27
171.7 87° 28' to W. 101

4126° 21'
120.406

21133° 07 1/4'
66.3314

343.67
213.30
526.97

342.94
378.94
721.88
721.59

343.07
378.94
722.01
721.72
721.59
202.49
133.15
335.64
334.17

395.28
17.53
393.75