



SECTION CORNER FOUND
OSBF P/C, 4 BTS, 1958

SECTION CORNER FOUND
OSBF P/C, 5 BTS, 1958

SECTION CORNER FOUND
OSBF P/C, 7 BTS, 1960

Polk County
Lincoln County

Polk County
Lincoln County

Polk County
Lincoln County
Benton County

COUNTY LINE CROSSING ESTABLISHED
SET OSBF P/C 30" IG
NO SUITABLE TREES WITHIN LIMITS IN EITHER SECTION
CREEK 5 LKS WIDE EAST 100', CRS SOUTH
WPCP NE 1.0'
POINT LOCATED ON STEEP, BRUSHY, LOGGED-OFF
HILLSIDE, ASPECT EAST

COUNTY LINE CROSSING ESTABLISHED
SET OSBF P/C 28" IG
18" ALDER S 26° E 1.8', S B, LINCOLN CO., RS
18" ALDER N 2° W 6.2', S B, POLK CO.
WPCP NW 1.0'

COUNTY CORNER ESTABLISHED
SET OSBF P/C 30" IG
40" FIR N 30° E, S B, POLK CO.
12" ALDER N 78° E 21.8', S B, POLK CO., RS
28" FIR S 22° W 67.2', LINCOLN CO.,
YMLP
NO SUITABLE TREE WITHIN LIMITS
IN BENTON CO.
WPCP SE 1.0'

1/4 CORNER FOUND
OSBF P/C, 2 BTS, 1975

1/4 CORNER REESTABLISHED
SET OSBF P/C 30" IG
NO SUITABLE TREES WITHIN LIMITS
IN EITHER SECTION
CREEK 3 LKS WIDE SOUTH 30', CRS NW
POINT LOCATED ON STEEP, BRUSHY, LOGGED-OFF
HILLSIDE ASPECT WEST
WPCP NW 1.0'

1/4 CORNER REESTABLISHED
SET OSBF P/C 33" IG
8" CASCARA S 73° E 29.1', S B, RS
6" ALDER S 74° W 29.8', S B YMLP
WPCP SE 1.0'
SPRING BRANCH EAST 22.0', CRS NE
SMALL RIDGE WEST 25.0', NE-SW

LEGEND

- OSBF P/C = OREGON STATE BOARD OF FORESTRY 1/2" x 3/8" GALVANIZED IRON PIPE AND 3" BRONZE CAP
- YMLP = YELLOW METAL LOCATION POSTER
- IG = IN GROUND
- WPCP = 4" x 4" x 72" WHITE PAINTED CEDAR POST
- BT(S) = BEARING TREE OR TREES
- CRS = COURSE
- RS = REGISTERED LAND SURVEYOR NO. 563
- ESTABLISHED COR. = NEW CORNER SET
- REESTABLISHED COR. = LOST GLO, CADASTRAL OR OTHER CORNER RESET BY PROPORTIONATE MEASUREMENT.

FOR DETAILED REPORT ON FOUND CORNERS SEE U. S. AND COUNTY RECORDS.
ALL NEW CORNERS AND ACCESSORIES MARKED ACCORDING TO "MANUAL
OF INSTRUCTIONS FOR THE SURVEY OF THE PUBLIC LANDS OF THE U. S."

SOLAR OBSERVATION

MAGNETIC VARIATION	20° 30' EAST
DATE	APRIL 11, 1975
STANDARD TIME	9:35:14 A M
LOCAL TIME	9:20:52 A M
SUN'S DECLINATION	N 8° 16' 29"
REF. & PAR. CORRECTION	- 1.02'
LATITUDE	44° 30' 00"
SUN'S ALTITUDE	39° 26' 49"
PLACE OF OBSERVATION	1/4 CORNER SECTIONS 10 AND 11, T. 10 S., R. 8 W., W. M.

REGISTERED PROFESSIONAL LAND SURVEYOR
W. E. Green
OREGON 1975 1162
W. E. GREEN
263

SURVEY FOR:
STATE OF OREGON - DEPARTMENT OF FORESTRY

COUNTY LINE SURVEY

SECTIONS 11 & 12, T. 10 S., R. 8 W., W. M.
POLK, LINCOLN AND BENTON COUNTIES, OREGON.
THEODOLITE, TAPE AND DISTANCE METER SURVEY BY: W. E. GREEN, M. B. BAUGHN,
M. E. STEELE, W. M. BONSANTI AND D. WIGER

DRAWN BY: W. E. GREEN
JULY, 1975
SCALE: 1" = 500'