

C.S. # 678

Hardcopy 10-5 #4

also see notes in file

F. B. 27-32

33

S. 39° 24' 17" W

Δ 9 is N. 008
+ E. 035
24.000

+ 1° 20' 8.000

+ 3° 35' 3.027

- .215

Striking E. of cor. .041

Δ 10 is S.W. .194

S.E. .100

11 S. 33° 37' 44" E 3.049

(S. 34° 30' E) - 3° 30' 8.000

12 1.014

Striking W. of cor. .381

S. 82° 18' H.W. 1.827

Back to Δ 10 which is .035 SW, 6.050 SE. of cor.

N 33° 48' 55" W
correction S. 5"
(N 33° 53' W.)
24.00

+ 2° 15' 8.000

+ 2° 15' 6.315

+ 6° 25' 7.514

- 4° 30' 1.036 + 1.246 X fence.

correction S. 41'
at 24.00 - 10° 35' 4.921

(N 35° 29' W) 4.349

18 2.566

19 - 1° 10' 7.228

20 3.714

21 + 4° 20' 4.283

Little Hill pasture 143.06

Wrightman Field 105.12 EE

7 Big Hill Pasture 637.18

Sodden field 88.46

35.2 12.11 38.82 23.992

Sodden field 61.00 7.997

3.021

Poll. Co. 28.21 35.010

215

34.795

objects

381

194

187

01539 = 53

12148 187.00

12148

65520

60740

47800

36444

113560

211

132

180

Note: North NW cor CI.50 CRB

4921

99289

44289

3936

98

44

48362

.98163

1.57

687141

490815

98163

15411591

98676

327

690732

197352

296028

32267052

7.994

.050

7.944

6.310

7.467

1.033

22.754

4.836

4.349

2.566

7.226

4.1731

3.714

4.265

49.710

N 51° 07' E - 112 157 Spring

N 51° 07' E - 9° 20' 3.77 Spring

S. 75° W

34

22

-2° 2025

23

-8°10' 4097

24

-11°37' 4790

25

.171

S 80°^{16'}09' W.1.198 to I^{10'}

Back to A 8

26 S. 72°^{71'}07' E. -3°35' 5,300S 87°^{23'}30' E .085 to cor. post.27 N 55°^{35 1/2'}28' E 13.34128 N 56°^{10 1/2'}58' E. 3.064N. 70°^{01'}08' W.
11.11129 8.0°^{3 2 1/2'}25' W. 11.690about .08 E.
of cor.30 N 87°^{11'}16' W. 941about .15 W.
of cor.31 S. 16°^{23'}16' W. 8000

.14 W. fence

32 7.503

.44 W. fence

33 S. 42°^{5° 01'}54' W. 6.35434 S. 32°^{32'}53' E. 6.444S 10°^{23'}30' E. 2.25 to cor. post.
S 40°^{23'}22' E. +40 to fence35 N. 78°^{40'}33' E. 11.330to fence
cor. 15.30 W.
.0536 N 30°^{52'}46' E. 14.273N 70°^{30'}30' E.
by needle37 N 30°^{20'}27' W. 2920S. 70°^{33'}42' E. 1.12 cor.
S. 39°^{23'}22' E. .52 cor.N 30°^{23'}27' W.
by needle38 N 9°^{31'}24' E. 3,662S. 34°^{30'}30' E. 6.66 cor.
N 33° E. 30 cor.39 N 32°^{57'}50' E. 3,413

.07 to fence

40 N 40°^{53'}46' E. 4,453

N. 82 burn

S 80°16' W.
N 33°48' W. S 56°12' W.
24°04' W

P.C.

4790
25979
43110
3353
431
23
469174078
1198
32624
36702
4078
4995444
91307
1198
730456
421763
91307
91307
10934578649710
2024
4056
4692
11171
60.653
48961.142
24.000
37.14237,158 37.142
299871
715490
699699
157410
99959
578530
498785
777450.02945 = 1°41'
1,093,85786
74284
351017
334278
167398
148568
188306at 6.00 fence 11.50
" 10.30 " 11.20.040
5.290
5.330

at 300 fence

at 60, 15 W. fence

at 4.26 fence 10.24

at 7.5 fence 10
at 7.28 " 11From 37 S. 63°^{7'}44' W. 21.
slanted cor.

35

41 N 70°^{23'}30' W -1°15' 7.671 +.37 cor.42 N 81°^{06'}13' W 5.192

N 30' E .397

N 26°^{14'}07' E. 16.060 - 2.03 cor.

W. 66 fence

To O 50°^{08'}15' E, 0 1/4" shaft 12.913

From Good's S.E. cor.

Backsighted N 53°57' W. on nail in oak

43 S. 66°53' E 1.595 offset N. 008 using S. 66° W. E

S. 66°36' E -2°15' 18.000
correction S. 6

44 (S. 66°30' E) -1°05' 5.628

45 S. 66°03' E -1°30' 7.094

S. 67°43' E .240
offset .068 S.
offset .005 N.

Set 3/4" pipe Oak stake S. 32°03' W. 404

S. 49°54' E +1°30' 3.267
N. 32°03' E. 459
N. 31° E. 459(S. 49°43' E) +1°30' 8.000
offset .073 S.W.
+ 229 N.W.
of cor.

46 +4° 3.980

47 -1°45' 2.202

48 -3°50' 2.097

49 S. 50°09' E. -9°40' 1.338
offset .006 N.

50 N 50°36' W. +3°50' 1.083.

51 (N 50°43' W) +2°50' 4.972

52 -3°15' 2.286

S. 66°11' E.

49°45'

16°28'

12.913

+.115

12.798

2.0
3.0
5.0S. 26°^{13'}5' N.N. 32°
415
413

1.575

15.988

5.627

7.091

.240

30.541

N 51°30' E. 47 to shaft & missed shaft

E. 47 about 1" offset .00180 = 6'

.008 N. 30.54 | 0.5500

.005 N. 30.54

.013 N. 24.60

.064 S. 27.432

.055 S. 2.80

S. 51° E 3.287 + 1.10 = O 30' from S. fence

offsets

.073 S.

.006 N.

1.338

.067 S. = 11"

.08587

12.042

1.070

.61

10

13188

1.34

5276

39.5

7.9

.005750

3.266

7.997

3.970

2.101

2.092

1.319

20.845

1.229

20.616

1.081

4.967

2.283

8.331

53	∠ Right 6" {	-7° 20'	4.683
54		-9° 15'	3.940
56	∠ Left 11"	-1° 40'	5.565
57			6.232
58		+5°	2.390
			-0.03

Striking E. of cor. .081

From 1/4" shaft on Cor. line

59	S. 49° 25' E	1.474
	S. 18° 57' W.	

60		12.470
61		8.124
62		16.369
63		4.921
64		11.513

Striking W. of stone .010

65	S. 83° 23' W. correction N 8' ∠ Right 15° 20 1/2'	24.836
66	S. 71° 20' W. or ∠ Left 12° 03'	24.000
67		6.901
68	S. 15° W. correction W. 9' ∠ Left 40° 30'	6.519

69		9.632
70	S. 23° 28' W.	9.060

offset .008 E
offset .607
offset .002 W

Smith's Backsighted along fence binder casting

offset N measured from stone

offset 6.450 S. Stone

offset 1.267 E
offset 1.334 W to corner

46.45	3940	offsets	
571	00789	.008 E	
46.45		.007 E	8.331
3251	05460	.005 E	4.645
232	3152	.002 W	3.889
008128	275	.013 E	5.563
	38887	.081 W	6.232
	271	.068 W	2.379
	3489		31.039
	2722		0.03
	194		31.036
006805	31.036	.00219 = 7 1/2	
		.068000	
		62072	
		59280	12.470
		31036	8.124
		282740	16.369
			4.921
			11.513
			53.397

Jan. 6, 1920.

S. 89° 52' W.

89° 60'	S. 83° 23' W.	S. 83° 23' W.
6° 37'	71° 20'	71° 20'
89° 60'	12° 03'	12° 03'
81° 16 1/2'	30.846	30.846
8° 43 1/2'		
6° 37'		

15° 20' 1/2	121000
24.836	54.166
	108332
	146680
	108332
	183480

N 71° 14 1/2' E. Tick bug on tree which may have been the wrong one.
N 82° 20' E. To A 1/2" Pin B.S. on corner

S. 15° W.	6.518	16.100
10° 30'	9.632	8.261
4° 30'	16.150	25.061

25° 28'	
S. 15° W.	9.06
8028	

offsets	
1334 W.	
1.267 E.	.00467 = 9'

2500.067 W.	
5012	
16000	
15.230	
19440	